

STAINLESS STEEL NON-THREADED IMC




Features:

- Manufactured in Type 304 and 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- No special tools or processes required for installation
- Standard NPT threads allow for trouble-free installations
- Lighter weight provides cost savings with labor and shipping
- Any custom size available up to 20' in length

Certifications and Compliances:

- UL / cUL 1242 Listed
- UL file number _ E363502
- Inclusive for installation in accordance with Article 344 of ANSI/NFPA 70
- "National Electrical Code" (NEC)
- NSF / ANSI 169 Certified



Applications:

Stainless steel IMC is often specified in corrosive environments where it is subjected to harsh chemical treatments or wash-downs due to its lighter weight, precise tolerances, and ease of installation. Calbrite's IMC is manufactured with or without threads. The non-threaded conduit can easily be used with compression couplings, allowing for lowered costs and simplified installations.

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical
- Pulp & Paper Mills
- Marine & Coastal Facilities

Type 304 Part Number	Type 316 Part Number	Trade Size	Metric Size	Outside Diameter	Inside Diameter	Weight Per Feet (lbs.)
S50510CT00	S70510CT00	1/2"	16	0.815"	0.660"	0.64
S50710CT00	S70710CT00	3/4"	21	1.029"	0.864"	0.88
S51010CT00	S71010CT00	1"	27	1.290"	1.120"	1.35
S51510CT00	S71510CT00	1-1/2"	41	1.883"	1.703"	2.02
S52010CT00	S72010CT00	2"	53	2.360"	2.170"	2.56

*All dimensions are for informational purposes only *Tolerances +/- 5%*