



1690

Large Case

Transport Case



- Retractable extension handle
- **4 strong polyurethane wheels with stainless steel bearings**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- **Large 2-person fold down handles**
- Stainless steel padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- **Watertight, crushproof, and dustproof**

CONFIGURATIONS

1690 - Standard

1694 - With With Padded Dividers

1690NF - With No Foam

DIMENSIONS

Interior (L x W x D): 30.13 x 25.13" x 15.36 (76.5 x 63.8 x 39 cm)

Exterior (L x W x D): 33.43 x 28.40" x 17.65 (84.9 x 72.1 x 44.8 cm)

Lid Depth: 2.86" (7.3 cm)

Bottom Depth: 12.14" (30.8 cm)

Total Depth: 15" (38.1 cm)

Int Volume: 6.73 ft³ (0.191 m³)

MATERIALS

Body: Polypropylene

Latch: ABS

O-Ring: Polymer

Pins: Stainless Steel

Foam: 1.3 lb Polyurethane

Purge Body: ABS

Purge Vent: 3 Micron Hydrophobic Non-Woven

Purge O-Ring: 70 Shore Nitrile

COLORS

■ Black

■ OD Green

■ Desert Tan

WEIGHT

Weight With Foam: 43.00 lbs (19.5 kg)

Weight Without Foam: 34.00 lbs (15.4 kg)

Buoyancy: 433.00 lbs (196.4 kg)

Master Pack Weight: 52.27 lbs (23.7 kg)

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 3.00" Convolute

Layer 2 (Base): 1.25" Pad

Layer 3 (Base): 3.65" Pick N Pluck

Layer 4 (Base): 3.65" Pick N Pluck

Layer 5 (Base): 3.65" Pick N Pluck

OTHER

Extendable Handle: yes

Master Pack: 1

Nameplate: yes

Reduced Area: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com